



EcoTouch® Insulation with PureFiber® Technology for Certified R Metal Building

Product Data Sheet



- R-10, 3.4"
- R-11, 3.7"
- R-13, 4.3"
- R-16, 5.3"
- R-19, 6.3"
- R-25, 8.0"
- R-30, 9.25"

Description

Owens Corning EcoTouch® Insulation with PureFiber® Technology for Certified R Metal Building is a light density fibrous glass blanket designed to be laminated with a variety of appropriate facings. Certified R is available in standard R-values of 10, 11, 13, 16, 19, 25 and 30. Standard roll widths are 36", 48", 60" and 72". Selected Made-to-Order widths are also available.

Key Features

- EcoTouch® insulation is the only fiberglass insulation product listed in the USDA BioPreferredSM Catalog.
- Formaldehyde-free².
- Made with 99% natural³ materials—not acrylic.
- Made in the U.S.A.¹

1. Meets requirements of the Buy American Act.
 2. Applies to the insulation component only.
 3. Unfaced insulation made with a minimum of 99% by weight natural materials consisting of minerals and plant-based compounds.

Typical Physical Properties

Property	Test Method	Result
Thermal Resistance	ASTM C177/C518	(see "Description")
Surface Burning	UL 723/ASTM E84	Flame spread index < 25 Smoke developed index < 50
Combustion Characteristics	ASTM E136	Non-combustible
Water Vapor Sorption	ASTM C1104	≤ 0.2% by volume
Fungi Resistance	ASTM C1338	Passes - no growth exhibited
Corrosiveness	ASTM C665	Passes
Odor Emission	ASTM C1304	Passes – no odor detected

1. The surface burning characteristics of these products have been determined in accordance with UL 723. The standard should be used to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions and should not be used to describe or appraise the fire hazard or fire risk of materials, products or assemblies under actual fire conditions. However, results of this test may be used as elements of a fire risk assessment which takes into account all of the factors which are pertinent to an assessment of the fire hazard of a particular end use. Values are reported to the nearest 5 rating.

- Uses a minimum of 65% recycled content—41% being post-consumer.
- GREENGUARD Children & Schools CertifiedSM.
- Easy to handle.
- Excellent recovery provides outstanding thermal and acoustical performance.

Product Applications

EcoTouch® Insulation with PureFiber® Technology for Certified R Metal Building is used as part of the insulation system in the roofs and side walls of metal buildings. It is designed to be laminated with a variety of facings to provide attractive interior finishes, abuse resistance, and assistance in control of moisture.

Owens Corning EcoTouch® Insulation with PureFiber® Technology for Certified R Metal Building are fabricated and distributed by a nation wide network of independent laminators assuring prompt service and delivery. Contact your Owens Corning Sales Representative for the names of insulation laminators servicing your area.

Installation

Several methods are used to insulate metal buildings. The usual method is to apply the insulation over the structural members (purlins and girts) and inside the exterior panels. This method generally accommodates single layer installations. Methods are also available to apply insulation between purlins so as to accommodate greater insulation thicknesses and better thermal performance.

Technical Information

Owens Corning EcoTouch® Insulation with PureFiber® Technology for Certified R Metal Building is regularly tested to ensure compliance to the NAIMA 202-96 (Rev. 2000) Standard. Sampling and testing is performed by the National Association of Home Builders Research Center (NAHB-RC). The product is labeled on the top surface of each roll with the nominal R-value and the "NAIMA 202-96" (Rev. 2000) to indicate compliance. The NAIMA 202-96 (Rev. 2000) standard specifies thermal