



TAYLOR METAL PRODUCTS PRODUCT GUIDE

Applications for all building markets:



www.taylormetal.com



KEY-HOLE™ TRACK SYSTEM *Lifetime Warranty*

KEY-HOLE™ TRACK FACEMOUNT

Keyhole Track offers versatility, strength and ease of use. Keyhole track is a 14-gauge galvanized track with face mount FNF Brackets for flashing or non-flashing applications. Designed for doors up to 600 lbs. Brackets are placed every two feet.



Size	Stock #
8'	HRTF8
10'	HRTF10
12'	HRTF12
16'	HRTF16

Size	Stock #
20'	HRTF20
22'	HRTF22
24'	HRTF24

KEY-HOLE™ TRACK STUDMOUNT

Keyhole Track offers versatility, strength and ease of use. Keyhole track is a 14-gauge galvanized track with zinc-lated bolts, nuts and washers. Designed for doors up to 600lbs. Brackets are placed every two feet.



Size	Stock #
8'	HRTS8
10'	HRTS10
12'	HRTS12
16'	HRTS16

Size	Stock #
20'	HRTS20
22'	HRTS22
24'	HRTS24

KEY-HOLE™ TRACK ACCESSORIES

KEY-HOLE™ FNF FLASHING BRACKET



A unique new bracket design for use with Facemount Key-Hole Track. Bracket installs in slots of facemount brackets after installation of track.

CannonBall # - 714777

Taylor # - HSILB

SPLICE COLLAR



Galvanized collar that combines two pieces of Key-Hole track. Features locking lugs to hold track firmly in place and prevent rotating.

CannonBall # - 465101

Taylor # - HSPLICE

END CAPS



Galvanized caps used to close off the open ends of Key-Hole track. Use two per track run to keep birds and debris out of track.

CannonBall # - 711489

Taylor # - HEC



KEY-HOLE™ TRACK SYSTEM *Lifetime Warranty*

KEY-HOLE™ TRACK ACCESSORIES CONT.

SINGLE TRACK BRACKET



Angled track bracket used to mount Studmount Key-Hole Track. The single track bracket is used to mount a single run of track. Brackets should be placed every two feet.

CannonBall # - 712138

Taylor # - HSB

DOUBLE TRACK BRACKET



Angled track bracket used to mount Studmount Key-Hole Track. The double track bracket is used to mount a double run of track. Brackets should be placed every two feet.

CannonBall # - 712137

Taylor # - HDB

COVER RETAINER BRACKET



Cover Retainer Brackets are used in conjunction with both the Single and Double Track Brackets to enhance the ability of using a track cover. Should be placed every two feet.

CannonBall # - 712136

Taylor # - HDILB

TROLLEY HANGERS

DELTRIN 9-1/2" ADJUSTABLE PENDANT BOLT TROLLEY



For use with Key-Hole Track Systems. Four-way offset adjustable pendant bolt for doors not weighing more than 600lbs.

CannonBall # - 713999

Taylor # - HPT

DELTRIN ADJUSTABLE MOUNTING BRACKET TROLLEY



For use with Key-Hole Track Systems. For solid wood doors up to 1-1/2" thick and not weighing more than 600lbs.

CannonBall # - 715608

Taylor # - HST




SLIDING DOOR SYSTEM

KWIK FRAME® SLIDING DOOR SYSTEM


Developed as a complete, cohesive assembly, the Kwik Frame system comes together in an easy, standard assembly - regardless of door panel sizing. Frames combine sturdy design and lightweight materials for straightforward construction on panels **under** 144 square feet.

200B SIDE RAIL



Size	Stock Number	
8'	CannonBall # - 724300	Taylor # - HDKSR8
10'	724304	HDKSR10
12'	724308	HDKSR12
14'	724312	HDKSR14
16'	724316	HDKSR16
20'	724740	HDKSR20
24'	713766	HDKSR24

216B DOUBLE COUPLE




Size	Stock Number	
10'	CannonBall # - 724324	Taylor # - HDKDC10
12'	724328	HDKDC12
14'	724332	HDKDC14
16'	724336	HDKDC16

244 BOTTOM RAIL




Size	Stock Number	
10'	CannonBall # - 724564	Taylor # - HDKBR10
12'	724565	HDKBR12
16'	724567	HDKBR16

235 STEEL GIRTS



Designed for ideal horizontal support on sliding door frames, the 235 Steel Girt is a 20-gauge galvanized steel beam sized for optimal door frame construction.

SOLD BY THE FOOT
Taylor # - HDKSH





SLIDING DOOR SYSTEM

SLIDING DOOR SYSTEM ACCESSORIES

DOOR GUIDE




Zinc plated steel construction and made from 11-gauge steel. Adjusts for doors 3" to 4-1/2". Guides the door along the building, reduces the amount of door sway.

CNB # - 715432

Taylor # - HVRDS

7" JAMB LATCH



Zinc plated steel construction. Adjustable design. Holds door firmly against jamb. Can be used for either right or left handed application.

CNB # - 728106

Taylor # - H7JL

GATE, STALL AND DOOR LATCH




Zinc plated steel construction with installation hardware. Can be used for either right or left handed applications. Latch is not spring loaded.

CNB # - 710586

Taylor # - HGSDL

OFFSET ADJUSTABLE STAY ROLLER




Adjusts for doors from 5/16" to 3-5/8". Mounting holes countersunk to protect door finish. 8-gauge zinc plated steel with black 2" diameter non-marring roller.

CNB # - 710806

Taylor # - H0ASR

JUMBO DOOR PULL



Assists with door opening and closing; a handle attached to door panels. Heavy gauge corrosion resistant steel.

CNB # - 710654

Taylor # - HJDP



International: 1-800-574-1388 • Local: 503-581-8338

Fax: 503-581-6877

4566 Ridge Drive NE Salem, OR 97301

