TAYLOR METAL PRODUCTS

Order Form

Inside Sales: _____

☐ New Order ☐ Add-on Order ☐ Quote

Fax to: 503-581-6877

PO# _____ **Date:** _____

Sold To: _____

Job Name: _____

Ship To: _____

Order Contact: _____

Phone # _____

Fax # _____

☐ **Will Call** ☐ **Delivery**

Day: _____ **Delivery Date:** _____

☐ **Agricultural** ☐ **Residential** ☐ **Commercial** **Route:** _____

☐ T-3
☐ Tuff-Rib
☐ PBR
☐ Marion "R" Panel
☐ GR-7
☐ GR-5
☐ HR-34
☐ 2-1/2" Corrugated
☐ Classic 7/8" Corrugated

Panels with * need Pattern Choice:
☐ Ribs ☐ Flat ☐ Striations
Notched? Y N Clip Relief? Y N
Sealant? Y N

☐ 12" Easy-Lock*
☐ 16" Easy-Lock*
☐ 16" StreamLine*
☐ ShadowLine*
☐ SmoothWall**
☐ Soffit**

Soffit/SmoothWall ** Pattern Choices:
☐ Flat ☐ 1-V groove ☐ 2-V grooves
Perforated? Y N

☐ 12" Versa-Span*
☐ 14-5/8" Versa-Span*
☐ 16" Versa-Span*
☐ 18" Versa-Span*
☐ 12" MS200*
☐ 14-5/8" MS200*
☐ 16" MS200*
☐ 18" MS200*

Color: _____
Pitch: _____
Gauge: _____
Dmatch: _____
Pallet: 10' 20' 30'

☐ 12-3/4" MS150*
☐ 16-5/8" MS150*
☐ 20" MS150*

Panel & Flashing Items

*All Kynar, Easy-Lock, Soffit, & Smoothwall, Clip Lock, MS150, Versa Span, MS200 flashings are 10'
*All Armor Tech 26 and 29 Gauge. StreamLine, T-3, Tuff Rib, GR7, PBR, Corrugated, & GR5 flashings are 12'6"

Quantity	Length	Item Description	Quantity	Length	Item Description

Forgetting Anything?
Underlayment? Screws? Clips? Caulking? Closures?

4566 Ridge Dr NE · Salem, OR 97301 · F:503-581-6877 · P503-581-8338 · www.taylormetal.com