

# TMP PROTECT™ HT

LIMITED  
LIFETIME  
WARRANTY  
INCLUDED

## TMP Protect™ HT SELF-ADHERING HIGH TEMPERATURE UNDERLAYMENT

- Meets and exceeds ASTM D1970
- ASTM E108 Class A
- UV exposure up to six (6) months
- Limited Lifetime Warranty
- Approved for use with Class A fire-rated, code-compliant shingle roof coverings
- 36" x 67' (0.91 m wide x 20.4 m long)

TMP Protect™ HT is a self-adhering, high temperature underlayment with superior thermal stability and adhesion properties in a temperature range from 40°F (4.4°C) to 260°F (127°C), making it the right choice for complete roof deck coverage under metal roofing applications. Its asphalt-based adhesive seals tight to the roof deck and around fasteners to protect against leaks caused by ice dams, extreme temperatures, and wind-driven rain. TMP Protect™ HT is engineered with multiple layers for strength and durability, has a silicone-treated split-release film for ease of installation, and features an anti-skid, walkable surface for roofer safety.

TMP Protect™ HT can also be used under asphalt shingles, wood shakes and shingles, and mechanically-fastened roof tile.

TMP Protect™ HT underlayment is self-adhering and engineered for performance in high temperatures.



Call weekdays 8:00 am to 5:00 pm Pacific Time  
800-574-1388 or 503-581-8338

4566 Ridge Drive NE, Salem, OR 97301  
[www.taylormetal.com](http://www.taylormetal.com)

Rev. 05/22