



LAP DETAIL



ROOF & WALL PROFILE



KEY FEATURES

- 29 and 26 Tru-Gauge™
- 1:12 minimum pitch recommended when installed with butyl sealant
- Custom lengths 1' to 45'
(*For longer length panels, please inquire*)
- Long length flashings available up to 20' 11"
- Standard trim, custom trim and accessory packages available
- Color matched neoprene washered screws
- Roof and Vertical or Horizontal Wall application
- Perforated options available (*please inquire*)
- Fiberglass & Polycarbonate panels available to match profile
- Manufactured in Salem OR and Riverside CA
- OverEZee™ retro-fit systems available

TESTING

-  Code compliance UL Evaluation Report
UL ER #25913-01
 - UL 790 Class A (ASTM E108) - Fire rated
 - UL 2218 Class 4 - Impact (hail) rated
 - ASTM E1680 - Air infiltration (roof)
 - ASTM E1646 - Water infiltration (roof)
 - ASTM E1592 - Negative structural uniform static air pressure
 - ASTM E330 - Positive structural uniform static air pressure
 - ASTM E331 - Water infiltration (wall)
 - ASTM E283 - Air infiltration (wall)
 - ASTM A653/A924 - G90 Galvanized
 - ASTM A792 - Zincalume/Galvalume AZ-50/55

WEIGHT CHART

TUFF RIB	WIDTH	29 GA STEEL	26 GA STEEL
THICKNESS		0.0136"	0.019"
WEIGHT/LINFT	36"	1.917 LBS	2.819 LBS
WEIGHT/SQFT	36"	0.639 LBS	0.940 LBS

ASTM E 1680/E283 Air Penetration	ASTM E 1646/E331 Water Penetration
25 PSF<0.01 CFM/ft ² -PASS	50 PSF - Pass