TAYLOR METAL PRODUCTS

2-1/2” Corrugated™
Roof & Wall Panel Technical Data Resource

LAP DETAIL



ROOF & WALL PROFILE



KEY FEATURES

- 29 and 26 Tru-Gauge™
- 3:12 minimum pitch recommended when installed with butyl sealant
- Custom lengths 1’ to 30’ (*For longer length panels, please inquire*)
- Long length flashings available up to 20’ 11”
- Standard trim, custom trim and accessory packages available
- Color matched neoprene washered screws
- Roof and Vertical or Horizontal Wall application
- Perforated options available (*please inquire*)
- Fiberglass panels available to match profile
- Manufactured in Salem OR
- OverEZee™ Retro-fit systems available

TESTING

- ASTM E1680 - Air infiltration (roof)
- ASTM E1646 - Water infiltration (roof)
- ASTM E331 - Water infiltration (wall)
- ASTM E283 - Air infiltration (wall)
- ASTM A653/A924 - G90 Galvanized
- ASTM A792 - ZINCALUME/Galvalume AZ-50/55

WEIGHT CHART

2-1/2 Corr	WIDTH	29 GA STEEL	26 GA STEEL
THICKNESS		0.0136”	0.019”
WEIGHT/LINFT	24”	1.325 LBS.	1.949 LBS
WEIGHT/LSQFT	24”	0.663 LBS	0.975 LBS

ASTM E 1680/E283 Air Penetration	ASTM E 1646/E331 Water Penetration
25 PSF<0.01 CFM/ft²-PASS	50 PSF - PASS