



Contour[™] Wall/Soffit Impact Series Chevron W[™]



EVALUATION ICC-ESR EVALUATION REPORT #5045 with CBC-CRC Supplement (coming 2024)





KEY FEATURES

- 24 and 22 Tru-Gauge™
- · .032" & .040" Aluminum
- 20 and 18 gauge, .050" and .063" Aluminum available (*Please Inquire*)
- Custom lengths 2' to 20'10"
- 2' Shortcut capability (Fee applicable)
- · Concealed Fasteners: fasteners cannot leak
- · High-wind clips are available
- · Versatile in wall and soffit applications
- "Oil Canning" is an inherent characteristic of roof and wall products, and not a defect, which is not a cause for panel rejection.

TESTING



- ASTM E1592 Structural uniform static air pressure
- ASTM E1680 Air infiltration (roof)
- ASTM E1646 Water infiltration (roof)
- ASTM E331 Water infiltration (wall)
- · ASTM E283 Air infiltration (wall)
- ASTM A653/A924 G90 Galvanized
- ASTM A792 Zincalume/Galvalume AZ-50/55
- ASTM B209 Aluminum Substrate




MATERIAL SPECIFICATIONS

- 24 Tru-Gauge™ Kynar 500® Painted Steel
- ▲ 22 Tru-Gauge[™] Kynar 500® Painted Steel
- + .032" Kynar 500® Painted Aluminum
- 24 Tru-Gauge™ G-90 Galvanized or AZ-50
- 24 and 22 Tru-Gauge[™] bare Zincalume® Plus AZ-55 (No finish warranty – 25 yr. perforation warranty)
- G-90 Galvanized or AZ-50
- .040" Kynar 500® Painted Aluminum (Please Inquire)
- 24 Tru-Gauge[™] Bonderized
- 22 gauge Rusteel Plus™ (A606) (No finish warranty – no perforation warranty)
- 16 OZ & 20 OZ Real Copper
- Kynar 500® and substrate testing data available (See website)

FINISHES

- 21 Standard Colors, 5 Metallic Colors and 4 Specialized Colors
- Kynar 500® Paint System the ultimate in exterior durability and color retention
- "Cool" color pigments are specially designed to reflect infrared light, reducing heat gain to dwelling, and conform with ENERGY STAR® criteria
- Superior quality, two coat, 70% resin finish, applied at a 1 mil. thickness
- · 40 year residential paint warranty
- 20 and 30 year commercial paint warranty: Contact TMP for warranty specifications
- "Oil Canning" is an inherent characteristic of roof and wall products, and not a defect, which is not a cause for panel rejection



STANDARD COOL KYNAR 500® COLORS

40-Year Residential / 20 and 30 Year Commercial Manufacturer's Limited Warranty





These printed chips provide a close representation of the colors.

Metal samples are available upon request. Coatings are low gloss 10-15% sheen. SRI = Solar Reflective Index. SRI values listed above are in accordance with ASTM E 1980 and are based on actual testing.***Oil canning is not a cause for material rejection***









Rev. Date 03-24