



LAP DETAIL



ROOF & WALL PROFILE



KEY FEATURES

- 29 and 26 Tru-Gauge™
- 3:12 minimum pitch recommended when installed with butyl sealant
- Custom lengths 1' to 30'
(For longer length panels, please inquire)
- Long length flashings available up to 20' 11"
- Standard trim, custom trim and accessory packages available
- Color matched neoprene washered screws
- Roof and Vertical or Horizontal Wall application
- Perforated options available (please inquire)
- Fiberglass panels available to match profile
- Manufactured in Salem OR
- OverEZee™ Retro-fit systems available

TESTING

- ASTM E1680 - Air infiltration (roof)
- ASTM E1646 - Water infiltration (roof)
- ASTM E331 - Water infiltration (wall)
- ASTM E283 - Air infiltration (wall)
- ASTM A653/A924 - G90 Galvanized
- ASTM A792 - Zincalume/Galvalume AZ-50/55

MATERIAL SPECIFICATIONS


- 29 & 26 gauge bare Zincalume® Plus AZ-55
(No finish warranty – 25 yr. perforation warranty)
- 29 & 26 gauge bare G-90 Galvanized
(No finish warranty – no perforation warranty)

KEY FEATURES


- Zincalume® Plus and Galvanized G-90

40-Year Residential Manufacturer's Limited Warranty

STANDARD COOL ARMORTECH™ SMP COLORS



Zincalume® Plus SRI-65
No finish warranty – 25 yr.
perforation warranty



Galvanized G-90
No finish warranty – no
perforation warranty

These printed chips provide a close representation of the colors.

Metal samples are available upon request. Coatings are low gloss 10-15% sheen.
SRI = Solar Reflective Index. SRI values listed above are in accordance with ASTM E 1980 and
are based on actual testing.***Oil canning is not a cause for material rejection***



Rev. Date 07-25