




ICC
EVALUATION
SERVICE®


ICC-ES EVALUATION REPORT #5045 with CBC-CRC Supplement

CLIP ATTACHMENT






PANEL ATTACHMENT CLIP

STANDOFF CLIP



STANDARD CLIP



KEY FEATURES

- Manufactured in Salem, OR, Sacramento, CA and Riverside, CA
- 12" panel coverage
- 1-1/2" rib height
- 24 Tru-Gauge™ steel & .032" aluminum are standard and attached with high-performance concealed clips (some profiles may be available with an integrated screw flange option--please inquire)
- Screw flange is not available in heavier gauges:
 - 22 Tru-Gauge™ steel and .040" aluminum
 - Custom 20 & 18 Tru-Gauge™ steel and .050" & .063" aluminum
- Aluminum is recommended within 1000 ft of salt water (*not required*)
- 3' to 32'9" panel lengths (*Inquire for longer or shorter lengths*)
- Custom profiles available
- Vertical or horizontal wall application
- Acceptable for use as a soffit panel
- Interchangeable panel widths and configurations
- Perforated options available (*please inquire*)

TESTING

-  ICC-ESR #5045 with CBC-CRC Supplement
- ASTM A653/A924 - G-90 Galvanized
- ASTM A792 - ZINCALUME®/Galvalume® AZ-50/55
- ASTM B209 - Aluminum Substrate
- ASTM D6578 - Anti-Graffiti
- ASTM E283 - Air infiltration (wall)
- ASTM E331 - Water infiltration (wall)
- ASTM E1592 - Structural uniform static air pressure
- ASTM E1646 - Water infiltration (roof)
- ASTM E1680 - Air infiltration (roof)

WEIGHT CHART

NX-3	TYPE	24 GA STEEL	22 GA STEEL	20 GA STEEL	18 GA STEEL	.063" ALUM	.050" ALUM	.040" ALUM	.032" ALUM
THICKNESS		0.0236"	0.0285"	0.0356"	0.0466"	0.063"	0.050"	0.040"	0.032"
WEIGHT/LINFT	CLIP ATTACH	1.670 LBS	1.956 LBS	2.444 LBS	3.199 LBS	1.511 LBS	1.199 LBS	0.959 LBS	0.791 LBS
WEIGHT/SQFT	CLIP ATTACH	1.670 LBS	1.956 LBS	2.444 LBS	3.199 LBS	1.511 LBS	1.199 LBS	0.959 LBS	0.791 LBS
WEIGHT/LINFT	SCREW FLANGE	1.816 LBS	2.314 LBS	2.890 LBS	3.783 LBS	1.787 LBS	1.418 LBS	1.135 LBS	0.860 LBS
WEIGHT/SQFT	SCREW FLANGE	1.816 LBS	2.314 LBS	2.890 LBS	3.783 LBS	1.787 LBS	1.418 LBS	1.135 LBS	0.860 LBS

ASTM E 1680/E283 Air Penetration	ASTM E 1646/E331 Water Penetration
12 PSF<0.01 CFM/ft²-PASS	20.5 PSF - Pass
Intertek Test Result L5460.01-901-44 R1	
Intertek Test Result L5461.01-901-44 R1	
STRUCTURAL TESTING ASTM E1592 AND E330	
Intertek Test Result N3050.16-301-44 R0	

NEGATIVE LOAD CHART WITH CLIP ATTACHMENT

				SECTION PROPERTIES						ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)								
Width, in.	Gauge	Yield ksi	Weight psf	Top in Compression			Bottom in Compression			Negative Load								
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'
12	24	50	1.65	0.1361	0.1310	0.1278	0.1175	0.1230	0.1542	130.0	118.1	106.3	94.4	82.5	70.6	58.8	46.9	35.0
12	22	50	1.94	0.1690	0.1619	0.1612	0.1447	0.1517	0.1899	150.0	137.5	125.0	112.5	100.0	87.5	75.0	62.5	50.0
12	20	33	2.37	0.2320	0.2320	0.2310	0.1960	0.2060	0.2384	150.0	137.5	125.0	112.5	100.0	87.5	75.0	62.5	50.0
12	18	33	3.08	0.3190	0.3030	0.3268	0.2660	0.2810	0.3105	150.0	137.5	125.0	112.5	100.0	87.5	75.0	62.5	50.0

- Theoretical section properties for still panels have been calculated per AISI S100 Specifications for Design of Cold-Formed Steel Structural Members. Intertek N3050.16-301-44 R0
- Charted Load/Span values are based on ASTM E1592-05, divided by a 2.00 Factor-of-Safety.
- Minimum recommended substrate (structure) recommendations:
 - Open-Framing (i.e. purlins)-16ga (design thickness 0.0566")
 - Plywood/OSB-15/32" or thicker is recommended to assure an effective degree of fastener thread engagement.
 - METAL DECK - 22ga (design thickness 0.0283")

POSITIVE LOAD CHART WITH CLIP ATTACHMENT

				SECTION PROPERTIES						ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)									
Width, in.	Gauge	Yield ksi	Weight psf	Top in Compression			Bottom in Compression			Positive Load									
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	1'	2'	3'	4'	5'	6'	7'	8'	9'	10'
12	24	50	1.65	0.1361	0.1310	0.1278	0.1175	0.1230	0.1542	797.3	398.6	265.8	199.3	127.8	88.8	65.2	49.9	39.4	32.0
12	22	50	1.94	0.1690	0.1619	0.1612	0.1447	0.1517	0.1899	1134.6	567.3	378.2	251.9	161.2	111.9	82.9	63.0	49.8	40.3
12	20	33	2.37	0.2320	0.2320	0.2310	0.1960	0.2060	0.2384	1142.7	571.4	380.9	238.2	152.5	105.9	77.8	59.6	47.1	38.1
12	18	33	3.08	0.3190	0.3030	0.3268	0.2660	0.2810	0.3105	1767.3	883.6	569.3	320.2	204.9	142.3	104.6	80.1	63.3	51.2

- Theoretical section properties for Steel panel have been calculated per 2020 AISI S100 North America Specifications for the Design of Cold-Formed Steel Structural Member.
- Allowable loads for Steel panels are calculated in accordance with 2020 AISI S100 specifications considering bending , shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- When panels are installed over solid or closely fitted sheathing, the capacity is limited to the capacity of the underlying sheathing.

PANEL ATTACHMENT



Fastener Notes:

- When possible, lap panels away from prevailing wind direction.
- 15/32" OSB: #10 Burr Buster fasteners.
- 15/32" Plywood: #10 GP Fastener. Screws should be long enough to penetrate through the bottom of the plywood by 3/8".
- Dimensional lumber: #10 GP. Screws should penetrate the lumber 1".
- 16ga (or less) Steel furring: #10 or #12 Fastener with DP-1
- All trim screws used for roof or wall applications should have EPDM sealing washers.