

Get closure

Custom Fit Foam
Closure System

- **Less Money**
Economically priced
without sacrificing quality
- **Less Worry**
Tests better than
competitors
and lasts longer
- **Less Cleanup**
Pre-scrapped for quicker
install and easier cleanup

*UV resistant and
incredibly durable.*

Closure-Foam™ comes in 400 standard profiles, six types of foam and custom sizes that are easy to order. Designed to stay put, Marco's M63™ industrial adhesive eliminates blow away problems. The generous 1/4" adhesive bead can be applied to either the flat or the ribbed side of Closure-Foam and it even adheres in subfreezing temperatures and on wet surfaces.

CLOSURE-FOAM™

Interlocking dovetails are also available to eliminate gaps, ensure a snug end-to-end fit and are available with or without adhesive. They ship pre-scrapped leaving you with less job site cleanup.

Closure-Foam is economically priced without sacrificing quality. Marco's crosslink polyethylene foam has a unique coating which gives it better UV resistance and better durability than the industry standard. Independent testing confirms Marco's 1.5 density foam provides better UV stability than competitive products with a 2.0 density.



PANELS: **PBR** **Classic 7/8 Corrugated**
 Tuff Rib **Classic V Rib**
 T-3 **BR-36**
 GR& **HR-34**



One element of the Marco WEATHER-TITE™ SYSTEM



FOAM CLOSURES

SEALANTS

VENTILATION

FLASHING

DOORS

FASTENERS

UNDERLAYMENT



SPECS & EASY INSTALL

See our installation animations online at MarcoIndustries.com



MASTIX
Butyl tape



ANGLEKUT
Beveled foam closure

Installation is easy with Mastix and Anglekut

| PROPERTY / TEST | STANDARD | UNITS | LD24 VALUE |
|------------------------------------------------------------------------------------------------------------|-----------------------|-------------------|-----------------------|
| Nominal Density - Skin/Skin | BS ISO 7214 1998 | kg/m ³ | 24 |
| Cell Size - Typical Diameter | Internal | mm | 0.3 |
| Compression Stress-Strain: 10% compression 25% compression 40% compression 50% compression | BS ISO 7214 1998 | kPa | 34 |
| | | kPa | 53 |
| | | kPa | 85 |
| | | kPa | 118 |
| Compression Set: 25% comp., 22hr, 23°C ½ hr recovery: 25 mm cell-cell 24hr recovery: 25 mm cell-cell | BS ISO 7214 1998 | % set | 13 |
| | | % set | 5 |
| Compression Set: 50% comp., 22hr, 23°C ½ hr recovery: 25 mm cell-cell 24hr recovery: 25 mm cell-cell | | % set | 27 |
| | | % set | 19 |
| Tensile Strength | ISO 7214 1998 | kPa | 320 |
| Tensile Elongation | | % | 130 |
| Tear Strength | BS EN ISO 8067 1995 | N/m | 495 |
| Shore Hardness 00 Scale: 10mm cell/cell thickness | ISO 868 1985 | 00 | 50 |
| Recommended operating temperature range* | Internal | °C | +100 max / -70 min |
| Thermal Conductivity - mean temp of 10°C | ISO 8302 1991 | W /m.K | 0.0392 |
| Flammability: Automotive | FMVSS.302 - Burn rate | <100mm/min. | Pass: 12 mm & thicker |
| Flammability: Horizontal Burn Rate | ISO 7214 1998 | mm/sec | 5mm thick / 2.1 |
| | | mm/sec | 13mm thick / 1.5 |
| Durometer | 50 | Shore 00 | |
| Water | | lbs/ft3 | 5% |


Closure Foam represents yet another Marco Industries development in bringing you innovative, higher quality, and more economical products for the building industry.

Marco Weather-Tite®
System Advantage

With Marco's Rapid Response™ get more of what you need faster and easier. Take advantage of free shipping with low minimum orders. Marco - we're big on customer service and small on hassle. Build it smart. Buy it smarter.

MarcoIndustries.com

1.800.800.8590



This protective coating forms under extreme pressure during the process of manufacturing and shields the product from harmful UV rays.

