

STRIATIONS




ACCENT RIBS



LOCK SEAM DETAIL


REVERSE LAP DETAIL



KEY FEATURES

- 16" Coverage Option
- 26 Tru-Gauge™ ArmorTech™ SMP Painted Steel
- Factory-notched and tabbed panels available
- Vertical interlocking application: allows installation from both directions starting at any location
- Patented no-siphon lock seam
- 1" vertical rib with 3/8" flat top for ease of flashing attachment
- Concealed fasteners: fasteners cannot leak
- Pre-slotted fastener flange: allows expansion & contraction of panel (high wind clips available for panel lengths over 35')
- 3:12 minimum pitch recommended
(For lower pitches, please inquire)
- Standard panel lengths 4' to 35' - not notched
Standard panel lengths 1' to 35' - notched
(For longer panels, please inquire)
- Manufactured in Salem OR, Auburn WA, Sacramento CA and Riverside CA
- Panel options: Striations and Accent Ribs

TESTING

-  Code compliance UL Evaluation Report UL ER #25913-01
- UL Construction No. 529
- UL 580 Class 90 - Wind Uplift
- UL 790 Class A (ASTM E108) - Fire rated
- UL 2218 Class 4 - Impact (hail) rated
- ASTM A653/A924 - G90 Galvanized
- ASTM A792 - ZINCALUME/Galvalume AZ-50/55
- ASTM B209 - Aluminum Substrate
- ASTM E2886 - Ember Resistant ridge/endwall/peak flashings available

WEIGHT TABLE

Streamline	WIDTH	26 GA STEEL
THICKNESS		0.0236"
WEIGHT/LINFT	16"	1.359 LBS
WEIGHT/SQFT	16"	1.019 LBS

Rev. Date 05-26