TAYLOR METAL PRODUCTS

2-1/2” Corrugated™ Roof & Wall



LAP DETAIL



ROOF & WALL PROFILE



KEY FEATURES

- 29 and 26 Tru-Gauge™
- 3:12 minimum pitch recommended when installed with butyl sealant
- Custom lengths 1’ to 30’ (*For longer length panels, please inquire*)
- Long length flashings available up to 20’ 11”
- Standard trim, custom trim and accessory packages available
- Color matched neoprene washered screws
- Roof and Vertical or Horizontal Wall application
- Perforated options available (*please inquire*)
- Fiberglass panels available to match profile
- Manufactured in Salem OR
- OverEZee™ Retro-fit systems available

TESTING

- ASTM E1680 - Air infiltration (roof)
- ASTM E1646 - Water infiltration (roof)
- ASTM E331 - Water infiltration (wall)
- ASTM E283 - Air infiltration (wall)
- ASTM A653/A924 - G90 Galvanized
- ASTM A792 - ZINCALUME®/Galvalume® AZ-50/55

TAYLOR METAL PRODUCTS

MATERIAL SPECIFICATIONS

- 29 & 26 gauge bare ZINCALUME® Plus AZ-55 (*No finish warranty – 25 yr. perforation warranty)*
- 29 & 26 gauge bare G-90 Galvanized *(No finish warranty – no perforation warranty)*

• ZINCALUME® & ZINCALUME® Plus are registered trademarks of Bluescope Ltd. Galvalume® is a registered trademark of BIEC International, Inc.

KEY FEATURES

- ZINCALUME® Plus/Galvalume® and Galvanized G-90

MATERIAL AVAILABILITY (ZINCALUME/Galvalume- 25 Year Limited Warranty)

ZINCALUME® Plus SRI-65
No finish warranty – 25 yr. perforation warranty



Galvanized G-90
No finish warranty – no perforation warranty

These printed chips provide a close representation of the colors.

Metal samples are available upon request. Coatings are low gloss 10-15% sheen.
*SRI = Solar Reflectance Index. SRI values listed above are in accordance with ASTM E 1980 and are based on actual testing.***Oil canning is not a cause for material rejection****

steelscape

Rev. Date 04-26