


				SECTION PROPERTIES						ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)								
Width, in.	Gauge	Yield ksi	Weight psf	Top in Compression			Bottom in Compression			Negative Load								
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft	1'	1.5'	2'	2.5'	3'	3.5'	4'	4.5'	5'
12	24	50	1.61	0.0431	0.0434	0.0344	0.0440	0.0437	0.0461	145.0	131.9	118.8	105.6	92.5	79.4	66.3	53.1	40.0
12	22	50	1.94	0.0544	0.0547	0.0432	0.0554	0.0551	0.0560	145.0	131.9	118.8	105.6	92.5	79.4	66.3	53.1	40.0
12	20	33	2.27	0.0806	0.0788	0.0658	0.0745	0.0763	0.0718	190.0	171.9	153.8	135.6	117.5	99.4	81.3	63.1	45.0
12	18	33	2.60	0.1230	0.1172	0.1027	0.1030	0.1088	0.0960	190.0	171.9	153.8	135.6	117.5	99.4	81.3	63.1	45.0
12	0.032"	19	0.76	0.0820	0.0820	0.0699	0.0820	0.0820	0.2963	80.0	71.6	63.1	54.7	46.3	37.8	29.4	20.9	12.5
12	0.040"	19	1.09	0.1080	0.1080	0.0924	0.1080	0.1080	0.3859	80.0	71.6	63.1	54.7	46.3	37.8	29.4	20.9	12.5
12	0.050"	19	1.42	0.1340	0.1340	0.1145	0.1340	0.1340	0.4698	160.0	143.8	127.5	111.3	95.0	78.8	62.5	46.3	30.0

- 1a. Theoretical section properties for steel panels have been calculated per AISI S100 Specification for the Design of Cold-Formed Steel Structural Members.
- 1b. Theoretical section properties for aluminum panels have been calculated per the latest edition of the Aluminum Association Design Manual.
2. I_{xx} (eff) values are "effective" stiffness properties for positive (downward) load induced deflection determination.
3. S_{xx} values are to be used for flexural (bending) stress determination.
4. Charted Load/Span values are based on ASTM E1592-05 (2017) testing protocol.
5. Charted Load/Span values above are based on Allowable Stress Design (ASD)....Load Resistance Factor Design (LRFD) technique not recommended for charted values.
6. Charted Allowable Uniform Loads are based on the Ultimate Uniform Load (per ASTM E1592-05 testing) divided by a 2.00 Factor-of-Safety.
7. Charted Allowable Uniform Loads do not consider panel weight (Dead Load) or clip-to-substrate (structure) fastener connection strength.
8. Clip-to-substrate (structure) fastener evaluation and analysis should be performed by a licensed structural engineer.
9. Minimum recommended substrate (structure) recommendations:
 - a. Open-framing (i.e. girts) - 16 ga. (design thickness = 0.0566")
 - b. Plywood/OSB - 15/32" or thicker is recommended to assure an effective degree of fastener thread engagement
 - c. Metal deck - 22 ga. (design thickness = 0.0283")
10. Deflection limit consideration for positive (downward) loading is limited to a deflection ratio of $L/180$ of the span....where "L" is the span in inches.
11. Charted Allowable Uniform Loads cannot be increased by 1/3.

				SECTION PROPERTIES						ALLOWABLE UNIFORM LOADS, psf For various clip spacings (i.e. span values)									
Width, in.	Gauge	Yield ksi	Weight psf	Top in Compression			Bottom in Compression			Positive Load									
				I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	I_{xx} in ⁴ /ft.	I_{xx} (eff) in ⁴ /ft.	S_{xx} in ³ /ft.	1'	2'	3'	4'	5'	6'	7'	8'	9'	10'
12	24	50	1.61	0.0431	0.0434	0.0344	0.0440	0.0437	0.0461	216.4	108.2	72.1	53.8	34.4	23.9	17.6	13.4	10.6	
12	22	50	1.94	0.0544	0.0547	0.0432	0.0554	0.0551	0.0560	318.2	159.1	106.1	67.5	43.2	30.0	22.0	16.9	13.3	10.8
12	20	33	2.27	0.0806	0.0788	0.0658	0.0745	0.0763	0.0718	325.5	162.7	108.5	68.5	43.9	30.5	22.4	17.1	13.5	11.0
12	18	33	2.60	0.1230	0.1172	0.1027	0.1030	0.1088	0.0960	570.0	285.0	190.0	107.0	68.5	47.6	34.9	26.7	21.1	17.1
12	0.032"	19	0.76	0.0820	0.0820	0.0699	0.0820	0.0820	0.2963	44.0	11.0								
12	0.040"	19	1.09	0.1080	0.1080	0.0924	0.1080	0.1080	0.3859	69.1	29.1	12.9							
12	0.050"	19	1.42	0.1340	0.1340	0.1145	0.1340	0.1340	0.4698	109.1	45.1	20.0	11.3						

- 1a. Theoretical section properties for Steel panelshave been calculated per 2020 AISI S100 North American Specification for the Design of Cold-Formed Steel Structural Member. I_{xx} and S_{xx} are effective section properties for deflection and bending.
- 1b. Theoretical section properties for Aluminum panels have been calculated per the 2020 edition of the Aluminum Association's Design Manual. I_{xx} and S_{xx} are effective section properties for deflection and bending.
- 2a. Allowable loads for Steel panels are calculated in accordance with 2020 AISI S100 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
- 2b. Allowable loads for Aluminum panels are calculated in accordance with the 2020 edition of the Aluminum Association's Design Manual considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
3. I_{xx} (eff) values are "effective" stiffness properties for positive (downward) load induced deflection determination.
4. Allowable loads for Steel panels are calculated in accordance with 2020 AISI S100 specifications considering bending, shear, combined bending and shear and deflection. Allowable load considers a 3 or more equal span condition.
5. S_{xx} values are to be used for flexural (bending) stress determination.
6. Allowable load does not address panel weight, fasteners, connection strength or support material.
7. Allowable load includes web crippling.
8. Load/Span values are based on theoretical computations and not load testing.
9. Deflection is not considered.
10. Allowable loads do not include a 1/3 stress increase for wind.
11. The Cascade1-12 Panel when installed as a three-span condition with spans of 8 ft. on-center for Steel and 4 ft. on-center for Aluminum are capable of withstanding the minimum uniform distributed load of 20 psf (0.958 kPa) noted in Table 1607.1 of the IBC and a minimum concentrated load of 300 lbf (1.33 kN).
12. When panels are installed over solid or closely fitted sheathing, the capacity is limited to the capacity of the underlying sheathing.



EXPIRES: 12/31/2026

Robert V. Nangia P.E.
7423 Hollow Ridge Drive
Houston, Texas 77095