





ICC-ES EVALUATION REPORT #5045 with CBC-CRC Supplement (Siding only)


ROOF LAP DETAIL



ROOF PROFILE



WALL LAP DETAIL



WALL PROFILE



KEY FEATURES

- Manufactured in Salem, OR, Sacramento, CA and Riverside, CA
- 24\"
- 24 & 22 Tru-Gauge™ steel and .032\"
- Custom 20 & 18 Tru-Gauge™ and .040\", .050\", & .063\" aluminum (*please inquire*)
- Aluminum recommended within 1000 ft of salt water (*not required*)
- 3' to 32'9\"
- 1:12 minimum pitch recommended when installed with butyl sealant
- Roof and vertical or horizontal wall application
- Standard trim, custom trim and accessory packages available
- Color matched neoprene washered screws
- OverEZee™ Retro-fit systems available

TESTING

-  ICC-ESR #5045 with CBC-CRC Supplement (Siding only - coming soon)
- ASTM A653/A924 - G-90 Galvanized
- ASTM A792 - ZINCALUME®/Galvalume® AZ-50/55
- ASTM B209 - Aluminum Substrate
- ASTM D6578 - Anti-Graffiti
- ASTM E283 - Air infiltration (wall)
- ASTM E331 - Water infiltration (wall)
- ASTM E1592 - Structural uniform static air pressure (Siding only - coming soon)
- ASTM E1646 - Water infiltration (roof)
- ASTM E1680 - Air infiltration (roof)

WEIGHT CHART

TMP .75-4-24	WIDTH	24 GA STEEL	22 GA STEEL	.032 ALUM
THICKNESS		0.0236"	0.0285"	0.032"
WEIGHT/LINFT	24"	2.908 LBS.	3.512 LBS	1.378 LBS
WEIGHT/LSQFT	24"	1.454 LBS	1.756 LBS	0.689 LBS

ASTM E 1680/E283 Air Penetration	ASTM E 1646/E331 Water Penetration
25 PSF<0.01 CFM/ft²-PASS	50 PSF - PASS

Rev Date: 07-26